



PART DIMENSIONS							
	MIN	MAX					
WIDTH	17.50						
DEPTH	21.54						
HEIGHT W/ 35 QT	19.64						
HEIGHT W/ 50 QT	23.54						
CONTAINTER CAPACITY	35 OR 50						
CONTAINER UOM	QUART						

MIN CABINET OPENING								
	FACE FRAME	FRAMELESS	INSET FACE FRAME	INSET FRAMELESS				
WIDTH	17.50	17.75	17.50	17.75				
DEPTH	21.75	21.75	22.50	22.50				
HEIGHT W/ 35	20.00	20.00	20.00	20.00				
HEIGHT W/ 50	23.75	23.75	23.75	23.75				

SLIDE SPECIFICATIONS							
SLIDE MANUFACTURER	BTL						
SLIDE PART NUMBER	BCIA-16-533	RELEASE PART NUMBER					
SLIDE TYPE	UNDERMOUNT	SLIDE EXTENSION	FE	MAX WEIGHT			
SLIDE CLOSING	SOFT/SELF	SLIDE LENGTH	21" [533MM]	RATING			
SLIDE MOUNTING	BOTTOM	SLIDE FINISH	ZINC	75 LB			

## CUSTOMER DRAWING

Г			,		INCH	AMERICAN PROJECTION	DRAWN	<b>BY</b> KRR	DATE   0 - 4 - 2	SIZE	REV-A-SHE	
					[MM]					В	OUT	QT PULL
						TOLERANCES DEC. D) .XX $\pm$ .03 [.8mm]	ANGLES ±1/2°	MATE			wing no. WCSC-21XXDM-2	0 .   88
	REV.	DATE	BY	DESCRIPTION OF CHANGE	(ALL) .)	R) .XX $\pm$ .02 [.5mm] (XX $\pm$ .005 [.13 mm] IONS $\pm$ 1/32 [.8 mm]	]	FINISH	1	PAR 4 V L	TNO. _WCSC-2 XXDM-2	SHEET 2 OF 2

This drawing is the property of Rev-A-Shelf (RAS) and is disclosed in confidence to the extent its subject matter is original to RAS. Any vendor receiving this drawing from RAS shall hold and use this drawing for the sole benefit of RAS and shall not disclose it to, or use or reproduce it for any third party, or perform any act adverse to the interest of RAS with respect to this drawing without the express written permission of RAS. Vendors shall not revise any physical, dimensional or performance characteristic unless authorized by Rev-A-Shelf Engineering.